


















# Ecological Paint with Cool Touch\*

## Benefits

-  Virtually No Odor
-  0 VOC
-  Dries Rapidly
-  HiderifficTechnology
-  Splatter resistant
-  Hypo-Allergenic
-  Water Cleanup
-  Brush, Roll or Spray
-  Kid Friendly
-  Netonian Rheology
-  Energy Saving
-  Virtually No Sag
-  No Known Carcinogens or Neuro-toxins
-  Microfiber reinforced
-  Longer Service Life

## Performance

Not only is Ecological Paint with Cool Touch\* friendly to the environment, adults and children, but also it performs well during and after application. It has exceptional flow and leveling qualities. Containing no solvents, the water based material can dry in hours. Its Cool Touch\* formulation provides extraordinary durability and energy efficiency.

## Surface Preparation

Prior to the start of any painting project, surface must be sound, clean, dry, and free from dirt, oil, chalk, or other contaminants. Hairline cracks should be filled with caulking compound level with the surface.

## Application

Ecological Paint with Cool Touch\* is applied with brush, sprayer, or roller. Ecological Paint is applied with brush, sprayer, or roller. Its unique Netonian rheology allows a splatter free application with virtually no lap marks. To obtain best results, do not thin. Airless spray tips recommended size is .018 (depending on fan size) with a fluid pressure of 1500-3000psi

## Colors

Custom colors are also available and free from glycol, APE surfactants and volatile organic compounds and neurotoxins. Our state of the art technology allows us to match nearly any color sample.

## Product Description

Ecological Paint with Cool Touch\* is one of the first water based acrylic urethanes, which has been formulated especially for chemically sensitive people and professional roofers. It creates a durable and flexible surface. It is odor free. This product does NOT contain any known hazardous, toxic or carcinogenic materials Its unique Cool Touch formulation decreases the heat absorbstion on the surface material by increasing its reflectivity within the IR spectrum. This lessens the contraction and expansion of the material, decreasing the chemical atmospheric degradation. The result is an energy conserving, extremely durable, longer lasting exterior coating.

## Technical Data

Vehicle Type	Acrylic Urethane
Pigment Type	Titanium Dioxide
Weight Solids	60%
Theoretical Coverage at	
Recomended Film Coverage	100 to 150
Dry Time @ 77° F	-Dry To Touch 2-4 hrs
Dries By	Water evaporation
Viscosity <sup>1</sup>	100 to 120ku
Flash Point(Seta)	None
Surface Temperature at Application	-Min 45f
Gloss (60° )=0-2	-Max150f
Clean Up With	Water
Weight Per Gallon	11.00# + - .1
VolatileOrganic Compounds (VOC)	0

HEALTH HAZARD	1 - Slight
FLAMMABILTY HAZARD	0 - Minimal
REACTIVE HAZARD	0 - Minimal
PERSONAL PROTECTION	E - Glasses, Gloves, Dust Respirator

[www.EcologicalPaint.com](http://www.EcologicalPaint.com)

Information contained in this technical literature is believed to be accurate and is offered in good faith for the benefit of the consumer. The Company, however, cannot assume any liability or risk involved with the use of the product since the conditions of use are beyond The Control Of The Company



Innovative Formulations Company  
1810 S. 6th Avenue South Tucson, AZ 85713  
(520)628-1553 FAX (520)628-1580

TECHNICAL DATA